

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : <b>B65D 83/76, 85/78, A23G 9/28</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 96/33928</b></p> <p>(43) International Publication Date: 31 October 1996 (31.10.96)</p>
<p>(21) International Application Number: PCT/AU96/00241</p> <p>(22) International Filing Date: 24 April 1996 (24.04.96)</p> <p>(30) Priority Data: PN 2623 24 April 1995 (24.04.95) AU</p> <p>(71)(72) Applicant and Inventor: VAN ZEELAND, Gregory, Russell [AU/AU]; 152 Wynnum Road, Norman Park, QLD 4170 (AU).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): KELLY, Damian, Anthony [AU/AU]; 2 Lucas Street, Lutwyche, QLD 4030 (AU).</p> <p>(74) Agent: CULLEN &amp; CO.; 240 Queen Street, Brisbane, QLD 4000 (AU).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> With international search report. With amended claims.</p>

(54) Title: A DISPENSING APPARATUS AND CONTAINER

(57) Abstract

A dispensing apparatus for dispensing contents from a container (10). The container rests upon a support (40) in the apparatus and has an outlet (14) at one end from which contents are directly dispersed and cover (15) at its other end. The apparatus has a ram (45) with a ram member (46) engageable against the cover (15) to move the cover (15) between a first position adjacent the other end to position adjacent the outlet (14) to dispense contents from the container (10). The pressure exerted on the cover (15) by the ram member (46) is released after a dispensing operation.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

## A DISPENSING APPARATUS AND CONTAINER

### FIELD OF THE INVENTION

THIS INVENTION relates to an improved dispensing apparatus. In particular, the invention concerns a frozen confection dispensing apparatus. The invention will be described by way of example with reference to an apparatus for dispensing a frozen soft serve confection. It should be appreciated that the apparatus of the invention may be used for dispensing other foodstuffs.

### BACKGROUND OF THE INVENTION

Australian patent specification 633038 discloses a frozen confection dispensing apparatus employing a collapsible container for holding the frozen confection. The container is not self supporting and is received in a hollow casing. A bellows arrangement is under constant pressurisation and acts upon the container to dispense confection from the container. The container has an outlet which is coupled via a dispensing conduit to a dispensing valve. This apparatus includes means for tempering frozen confection in the container to transform the confection from a hard frozen condition at a first sub-freezing temperature to a soft serve condition at a higher second sub-freezing temperature. Thermal insulation is disclosed for maintaining the container at the second temperature.

With such an arrangement a dispersive valve is necessary and requires periodic cleaning. This apparatus is not particularly effective in dispensing confection having entrained solid particles such as pieces of nuts or the like. Such solids tend to adversely affect the operation of the valve. The container needs to be supported by a hollow casing and thus adds to the complexity of the apparatus. The dispensing conduit requires regular cleaning.

The pressure applied to the container by the bellows is constant and not relaxed between serves. Soft serve confection is aerated to give it a desired consistency and quality. The application of constant pressure on the container leads to loss of this aeration and overrun during

dispensing. Thus results in wastage and deterioration of the iced confection.

Australian patent specification 618979 discloses another dispensing apparatus for frozen confection. The apparatus of this patent specification suffers from the same disadvantages as the apparatus of the specification just discussed. The apparatus of specification 618979 has a bellows shaped dispensing container from which the contents is dispensed via a passage terminated in a dispensing valve. The bellows shaped container does not allow all of its contents to be dispensed and wastage also occurs for this reason.

Australian patent specification 577058/94 discloses yet another apparatus for dispensing soft serve frozen confection. That apparatus employs a container having a deformable upper portion and has an integrally formed outlet from which contents within the container may be directly dispensed by application of pressure on the upper portion of the container by a plunger. The outlet is normally sealed by a cover which is removed prior to commencing a dispensing operation. Once again, the plunger functions continuously pressurise the container.

It is an object of the present invention to provide a dispensing apparatus which at least minimises some of the disadvantages referred to above.

#### DISCLOSURE OF THE INVENTION

According to one aspect of the invention there is provided a container from which contents may be dispensed, the container including a body, a lower wall at one end of the body, a dispensing outlet in the lower wall and a cover extending across the other end of the body spaced from the lower wall and movable between a first position adjacent the other end to a final position adjacent the one end to dispense contents from the container whereby a periphery of the cover remains in contact with an interior wall of the body as it moves between the first and the second positions.

The body may have any desired transverse cross sectional

shape. The periphery of the cover conforms to that peripheral shape. It is preferred that the body be circular in transverse cross sectional shape and in which case the periphery of the cover is also circular. Preferably the body is tapered such that the lower wall at the one end is smaller in area  
5 than the other end.

The dispensing outlet in the lower wall is preferably offset from a central location in the lower wall. The outlet may have a cap which normally seals the outlet prior to the dispensing of contents from the container. Alternatively, the outlet may be provided by frangible sections  
10 normally connected to each other and severable from each other but remaining hinged to the lower wall to allow contents to be dispensed. As an alternative to frangible sections a frangible or rupturable membrane may be present in the lower wall for allowing contents to be dispensed.

The cover, where the container body is tapered, may have a  
15 hinged peripheral lip extending around it for contacting the interior wall of the body. As the cover is driven into and along the body and towards the lower wall, the lip hinges relative to the remainder of the cover. In this way, the effective area defined by the cover matches the transverse area of the body as the cover moves from the larger to the smaller end of the body.

20 If desired, a lid may be fitted to the other end of the body to shield the cover during transport and storage of the container. The lid may be removed to enable the cover to be moved in the manner described to effect dispensing. The lid may be fixed to the body with a tamper evident seal.

25 According to another aspect of the invention, there is provided a dispensing apparatus including a housing having a support for a container of the type described above, a ram having a ram member movable into engagement with the container to dispense contents therefrom and to a position where pressure is released from the container after a dispensing  
30 operation and a refrigeration system for cooling the interior of the housing.

The ram may be driven in any suitable way. For example a mechanical drive such as a screw drive or a pneumatic or hydraulic drive

may be used. A hydraulic drive is preferred. The ram may be a hydraulic cylinder assembly and the ram member may comprise a plate adapted to engage the cover of the container. The drive ensures that after a dispensing operation has been completed, the ram member is withdrawn to  
5 relieve pressure on the container. In this way the tendency for soft serve ice cream in the container becoming flat is minimised.

Preferably force draft cooling is employed. Force draft refrigeration is achieved by employing a system including a fan and refrigeration unit adjacent the container. Preferably the housing is divided  
10 into two spaces and the container is located in one of these. One space may house a condensing unit of the refrigeration system while the space for the container may house a cross fin coil and fan for the force draft refrigeration. The control circuitry for the hydraulic drive may be housed in the one space within the housing.

15 DISCLOSURE OF THE DRAWINGS

Particular preferred embodiments of the invention will now be described by way of example with reference to the drawings in which:

Figure 1 is a vertical sectional view of a container according to an embodiment of the invention;

20 Figure 2 is a detailed view of an outlet from the container of Figure 1;

Figure 3 is a perspective view of a housing for a dispensing apparatus according to an embodiment of the invention;

25 Figure 4 is a front elevational view of details of the dispensing apparatus;

Figure 5 is a side view of the apparatus shown in Figure 4;

Figure 6 shows a hydraulic control circuit for operation of the ram;

30 Figure 7 shows a refrigeration circuit for cooling the interior of the dispensing apparatus;

Figure 8 shows a control circuit for operating the refrigeration circuit and the hydraulic circuits; and

Figure 9 shows a perspective view of a housing for the dispensing apparatus.

#### DETAILED DESCRIPTION OF THE DRAWINGS

Figure 1 shows a container 10. The container has a tapered body 11 so that a plurality of like configured bodies or empty containers may be stacked together. A Lower wall 12 extends across one end of the body 11. Lip 13 extends around the wall 12 and spaces the wall 12 from a surface upon which the container 10 may be placed. An outlet 14 extends from the wall 12 and is offset from the centre of the wall 12. Although outlet 14 is shown as a spigot it may be substantially flush or in the same plane as the wall 12.

A cover 15 extends across the other end of the body 11 to close off a space 16 within the body for retaining contents to be dispensed from the outlet 14. The cover 15 has a main portion 17 around the periphery of which is hinged a lip 18. The lip ensures that the cover seals the container throughout its movement from the position shown to its final position adjacent the innerface of wall 12.

The outlet 14 has a face or end 19. Greater detail of end 19 is shown in Figure 2. The end has sections 20 to 27 interconnected to each other by frangible connections 28. The sections, when the frangible connections are broken, remain hinged to the remainder of the outlet about connections extending along circular path 29.

A lid 17a is positioned onto an end of the container and has a lip 18a which fits over the end of the body to protect the cover 15 during transportation and storage of the container 10. When the container is positioned relative to a dispensing apparatus, the lid is removed.

Figure 3 shows a housing 30 for the dispensing apparatus of the invention. The housing 30 is shown viewed from the rear and has a cover or door 31 which provides access into the housing for the installation and removal of containers like that shown in Figure 1. Refrigeration and other control equipment may be located in the upper part 32 of the housing 30. Legs 33 extend downwardly from the housing and define a space 34



for a drip tray (not shown).

Figure 4 shows the dispensing apparatus of an embodiment of the invention. The container 10 rests on a support surface 40 and the container 10 is positioned to present the outlet near the front of the apparatus for easy access. An upper support surface 41 defines an upper part of the apparatus. A refrigerant compressor 42, a hydraulic power pack 43 including a pump, motor and sump and a refrigeration condenser unit 44 are located within this upper part. A ram 45 extends into the lower part of the housing from the upper part and terminates in a ram member 46.

That part of the apparatus where the container is located is subjected to fan forced refrigeration to circulate cool air about the container 10 to keep it cool. A drip tray D is located below a dispensing point 47. Housing 30 consists of an insulated stainless steel cabinet with a door extending over the upper part of the cabinet to conceal the refrigeration components and over the container. A hot gas heating circuit extends around the door surround.

Figure 5 shows a side view of the apparatus of Figure 4. The apparatus has a drip tray 50 for collecting condensation from the refrigeration unit 44 and from fan forced refrigeration unit 51. A further drip tray 52 with an outlet 53 is located above tray 50.

The hydraulic power pack 43 shown in Figure 4 is shown in greater detail in Figure 5. The unit has a motor 54 for driving a hydraulic pump which is in fluid communication with inlet/outlets 55, 56 of the ram 45 and a sump or reservoir 57. Switching unit 58 includes solenoid units and other controls for operating the apparatus.

Fan forced refrigeration unit 51 ensures that the lower part of the apparatus where the container is housed is kept cool and also provides for hot gas defrost if required. A serving area 59 is located beneath the container outlet 14.

It should be appreciated that several units like that shown may be placed side by side and share common refrigeration units 42 and fan forced refrigeration 51. Alternatively a unitary apparatus with provision for

multiple containers and multiple rams may be provided so that a variety of soft serve confections may be dispensed.

Figure 6 shows a circuit for the hydraulic ram 45. The circuit shows that ram 45 is double acting and hydraulic pressure may be supplied to either end of the ram by solenoid controlled diverter valve 60. Valve 60 is coupled to hydraulic pump 61 which supplies hydraulic fluid to valve 60 via line 62. Line 63 returns fluid to the pump 61. Reservoir 64 maintains a supply of fluid for the pump and fluid supplied by the pump to line 62 is obtained from the reservoir. Fluid returned via line 63 is returned to the reservoir.

Figure 7 shows a refrigeration circuit. The circuit consists of a compressor 70, a hot gas solenoid 71, a filter dryer 72, a condensor 73 with a condensor fan 74 and an evaporator 75 with a fan 76. Circuit 77 provides a heating circuit for a door frame of the dispensing apparatus.

Figure 8 shows an electric control circuit having a controller 80 which functions to correctly operate the compressor condensor fan, hot gas solenoid, and evaporator fan shown in Figure 7. A step down transformer 81 provides 12 VAC for the controller 80. Start switch 82 operates pump contactor 83 to control the hydraulic pump 61. Solenoid 85 is necessary for the proper operation of the diverter valve 60. Contactor 84 is controlled by contactor 83 and manual reverse/auto plunger release switch 86 to allow the ram member to release the pressure after a dispensing operation and for manual reverse of the ram member. The manual reverse switch is operated to retract the ram member to allow an empty container to be replaced with a full one.

Figure 9 shows housing having a cabinet 90 with a door 91. With the door 91 open a lower space is visible and a container from which the contents is to be disposed rests upon surface 40.

The apparatus of the invention operates as follows. With the ram fully retracted a full container may be positioned into the apparatus. When contents from the container are to be dispensed, the ram is operated to press against the cover of the container to cause the frangible sections in

the container outlet to be separated from one another and hinge to allow contents to be dispensed.

When sufficient contents have been dispensed the ram is reversed slightly to relieve the pressure that the ram member applies to the container cover. This ensures that pressure is relieved from the contents within the container. The sections in the outlet then close off the outlet and because the container is normally under no pressure no over-run is forced from the contents and the contents do not assume a flat texture.

Once the cover has travelled down the container after further dispensing operations and the container is emptied the ram is fully retracted, the empty container removed and a fresh container is positioned within the apparatus. Only the drip trays and the serving area may require periodic cleaning.

The apparatus does not require dispensing valves since the contents are directly dispensed from the container. Since no valve is present contents with solid inclusions may easily be dispensed.

## CLAIMS:

1. A container from which contents may be dispensed, the container including a body, a lower wall at one end of the body, a dispensing outlet in the lower wall and a cover extending across the other  
5 end of the body spaced from the lower wall and movable between a first position adjacent the other end to a final position adjacent the one end to dispense contents from the container whereby a periphery of the cover remains in contact with an interior wall of the body as it moves between the first and the second portions.
- 10 2. The container of claim 1 wherein the container is circular in transverse cross section and the cover has a circular peripheral shape.
3. The container of claim 1 wherein the dispensing outlet is offset from a central location in the lower wall.
4. The container of claim 3 including a cap which normally seals  
15 the outlet prior to the dispensing of contents from the container.
5. The container of claim 3 wherein the outlet is provided with frangible sections normally connected to one another and severable from each other but remaining hinged to the lower wall to allow contents to be dispensed from the container.
- 20 6. The container of claim 3 wherein the outlet is provided by a rupturable membrane formed in the lower wall which when ruptured, allows the contents to be dispensed from the container.
7. The container of claim 1 wherein the body is tapered between  
its ends.
- 25 8. The container of claim 7 wherein the cover has a hinged peripheral lip extending around it for contacting the interior wall of the body.
9. The container of claim 1 including a lid fitted over the cover to shield the cover while the container is being transported or stored.
10. The container of claim 9 wherein the lid is fitted to the body by  
30 a tamper evident seal.
11. A dispensing apparatus including a housing having a support for a container as claimed in any one of claims 1 to 10, a ram having a ram

member movable into engagement with the container to dispense contents therefrom and to a position where pressure is released from the container after a dispensing operation and a refrigeration system for cooling the interior of the housing.

5     12.           The dispensing apparatus of claim 11 wherein the support for the container is located in a lower part of the housing and an upper part of the housing receives refrigeration components and drive means for the ram.

13.           The dispensing apparatus of claim 12 having a dispensing point located below the container support surface.

10    14.           The dispensing apparatus of claim 12 wherein the apparatus includes fan forced refrigeration located in the lower part of the housing for cooling the container.

15    15.           The dispensing apparatus of claim 12 wherein an upper part of the housing provides a support relative to which the ram is mounted and through which the ram extends.

16.           The dispensing apparatus of claim 15 wherein the upper part of the housing contains a hydraulic powerpack including a reservoir, pump and solenoid valve for supplying hydraulic fluid under pressure to the ram to provide for movement of the ram member.

20    17.           The dispensing apparatus of claim 12 wherein the upper part of the housing contains a refrigerant circuit including a compressor and condensor unit.

**AMENDED CLAIMS**

[received by the International Bureau on 6 August 1996 (06.08.96);  
original claim 1 amended; remaining claims unchanged (2 pages)]

1. A container from which contents may be directly dispensed, the container including a body, a lower wall at one end of the body, a dispensing outlet in the lower wall and a cover extending across the other end of the  
5 body spaced from the lower wall and from which the contents may be directly dispensed into a receiving container from which the contents may be consumed and movable between a first position adjacent the other end to a final position adjacent the one end to dispense contents from the container whereby a periphery of the cover remains in contact with an interior wall of  
10 the body and the contents as the cover moves between the first and the second portions.
2. The container of claim 1 wherein the container is circular in transverse cross section and the cover has a circular peripheral shape.
3. The container of claim 1 wherein the dispensing outlet is offset  
15 from a central location in the lower wall.
4. The container of claim 3 including a cap which normally seals the outlet prior to the dispensing of contents from the container.
5. The container of claim 3 wherein the outlet is provided with frangible sections normally connected to one another and severable from  
20 each other but remaining hinged to the lower wall to allow contents to be dispensed from the container.
6. The container of claim 3 wherein the outlet is provided by a rupturable membrane formed in the lower wall which when ruptured, allows the contents to be dispensed from the container.
- 25 7. The container of claim 1 wherein the body is tapered between its ends.
8. The container of claim 7 wherein the cover has a hinged peripheral lip extending around it for contacting the interior wall of the body.
9. The container of claim 1 including a lid fitted over the cover to  
30 shield the cover while the container is being transported or stored.
10. The container of claim 9 wherein the lid is fitted to the body by a tamper evident seal.

11. A dispensing apparatus including a housing having a support for a container as claimed in any one of claims 1 to 10, a ram having a ram member movable into engagement with the container to dispense contents therefrom and to a position where pressure is released from the container after a dispensing operation and a refrigeration system for cooling the interior of the housing.
12. The dispensing apparatus of claim 11 wherein the support for the container is located in a lower part of the housing and an upper part of the housing receives refrigeration components and drive means for the ram.
13. The dispensing apparatus of claim 12 having a dispensing point located below the container support surface.
14. The dispensing apparatus of claim 12 wherein the apparatus includes fan forced refrigeration located in the lower part of the housing for cooling the container.
15. The dispensing apparatus of claim 12 wherein an upper part of the housing provides a support relative to which the ram is mounted and through which the ram extends.
16. The dispensing apparatus of claim 15 wherein the upper part of the housing contains a hydraulic powerpack including a reservoir, pump and solenoid valve for supplying hydraulic fluid under pressure to the ram to provide for movement of the ram member.
17. The dispensing apparatus of claim 12 wherein the upper part of the housing contains a refrigerant circuit including a compressor and condensor unit.




Fig. 1




Fig. 2






Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/AU 96/00241

<b>A. CLASSIFICATION OF SUBJECT MATTER</b>		
Int Cl <sup>6</sup> : B65D 83/76, 85/78; A23G 9/28		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b>		
Minimum documentation searched (classification system followed by classification symbols) IPC B65D 83/76, 85/78; A23G 9/28		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched AU: IPC as above		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) DERWENT		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	AU, 78107/89, B, (618979) (McGILL) 15 June 1989 See whole document	
X	AU, 49988/90, A (SCANDIA INVESTMENTS SA) 23 August 1990 See figure 1	1-6, 9, 10
X	DE 4118225 A (BASOTHERM GMBH) 10 December 1992 See figures 1 and 2	1-6, 9, 10
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex		
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&amp;" document member of the same patent family</p>		
Date of the actual completion of the international search 5 July 1996		Date of mailing of the international search report 18 JUL 1996
Name and mailing address of the ISA/AU AUSTRALIAN INDUSTRIAL PROPERTY ORGANISATION PO BOX 200 WODEN ACT 2606 AUSTRALIA Facsimile No.: (06) 285 3929		Authorized officer  D. LUM Telephone No : (06) 283 2544



**INTERNATIONAL SEARCH REPORT**  
**Information on patent family members**

International Application N  
**PCT/AU 96/00241**

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
AU	28107/89	AT	81941	BR	8807351	CA	1316403
		CN	1035090	DK	3925/89	EP	348468
		GB	2213532	GR	89100146	HK	333/93
		IL	88605	NZ	228241	US	5069364
		US	5215222	WO	8905096	IN	171933
		ZA	8808861				
AU	49988/90	CA	2010476	EP	384691	GB	8903826
		IL	93469	US	5165572	ZA	9001284
EP	509967	IT	1249137				
WO	9415856	DE	4300873				
END OF ANNEX							

# INTERNATIONAL SEARCH REPORT

International Application No.

PCT/AU 96/00241

C (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 4229588 A (FISCHBACH KUNST SPRITZGUSSWEK KG ALFRED) 10 March 1994 See figures 1-3	1-6, 9, 10
X	EP 509967 A (CENTRO DESIGN di ALDO CIABATTI & C. - S.a.s.) 21 October 1992 See figure 1	1-6, 9, 10
X	GB 992 262 A (NEILSONS GAIETY LTD) 19 May 1965 See figure 1	1-6, 9, 10
A	GB 2230057 A (McGILL) 10 October 1990 See whole document	
X	WO 94/15856 A (HENKEL KOMMANDITGESELLSCHAFT AUF AKTIEN) 21 July 1994 See figures 1 and 2	1-6, 9, 10
A	US 2568293 (NELSON) 18 September 1951 Whole document	
X	US 2716385 (TARR) 30 August 1955 Whole document	9-17